IN THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- 1.(Currently Amended) A light-guiding assembly for vehicle roofs comprising:
 - [[-]] a plurality of glass sheets (1, 2),
- [[-]] an interlayer (3)—of a polymeric laminating material interposed between the glass sheets—(1, 2),
- [[-]] light-coupling means (5)—for coupling light substantially into the light-guiding assembly interlayer,
- [[-]] the light coupled into the interlayer (3) being guided substantially through the interlayer (3) in order to avoid the light from traveling through the glass sheets.
- 2.(Currently Amended) A—The light-guiding assembly as claimed in claim 1, characterized in that the wherein a refractive index of

the interlayer (3) is higher than the a refractive index of the glass sheets (1, 2).

- 3. (Currently Amended) A—<u>The</u>light-guiding assembly as claimed in claim 2, characterized in that wherein the refractive index of the interlayer (3)—is higher than 1.57.
- 4. (Currently Amended) A The light-guiding assembly as claimed in claim 1, characterized in that further comprising a refractive layer (8; 9) of a material with a refractive index lower than the refractive index of the interlayer (3) is , the refractive layer being provided between the glass sheets (1, 2) and the interlayer (3), adjacent the interlayer (3).
- 5. (Currently Amended) A The light-guiding assembly as claimed in claim 4, characterized in that wherein the refractive index of the refractive layer (8, 9) is lower than 1.50.
- 6. (Currently Amended) A The light-guiding assembly as claimed in claim 4, characterized in that the refractive index of the

interlayer (3) and the refractive index of the glass sheets (1, 2) are approximately the same.

- 7. (Currently Amended) A—The light-guiding assembly as claimed in claim 1, characterized in that wherein the light-coupling means (5) are adapted to couple the majority of the light into the interlayer—(3).
- 8. (Currently Amended) A The light-guiding assembly as claimed in claim 1, characterized in that wherein the light-guiding assembly is provided with a recess (10), the recess (10) being adapted to receive the light-coupling means (5).
- 9. (Currently Amended) A The light-guiding assembly as claimed in claim 1, characterized in that wherein one of the glass sheets is made of a light-absorbing material.
- 10.(Currently Amended) An automotive vehicle roof comprising a_the_light-guiding assembly as claimed in claim 1.

11.(Currently Amended) An The automotive vehicle roof as claimed in claim 9, characterized in that wherein the automotive vehicle roof is substantially translucent.